

# Product datasheet


## Specifications

### Automatic Transfer Switches


#### TN type 3200A 3P 600V

HK-3200TNB3


Standard	IEC 60947-6-1 / UL1008	
Model	TN type	
Rated operational current, $I_n$	3200A	
Number of poles	3	
Rated frequency	50/60Hz	
Rated Operational Voltage, $U_e$	AC690V, DC250V	
Rated Insulation Voltage, $U_i$	800V	
Impulse Withstand Voltage, $U_{imp}$	8kV	
Switch capacity	Class	AC3, DC1
Switching frequency	100 times/h	
Switching sequence	A ↔ B, A ↔ OFF ↔ B	
Operating Time	Break(Opening)	≤ 35ms
	Make Closing	≤ 150ms
	Make delay(Off)	≤ 30ms
Rated short-time withstand current, $I_{cw}$	50kA	
Rated short-circuit making capacity, $I_{cm}$	50kA	
Operating Voltage & Current	AC110/120V	35A
	AC220/240V	18A
Control voltage	85 ~ 110% Rated operating voltage	
Withstand Voltage for Main circuit	3000V/60s	
Withstand Voltage for Control circuit	1500V/60s	
Life time	Electric	3000 times
	Mechanic	5000 times
Weight	84kg	
Dimension (W x L x H)	500x412x465mm	




Front View



Side View



3200A Bottom View



3200A Back View

