

Product datasheet

Specifications

Intelligent Capacitor BIC1 3PN 10kVAr 250V

BIC1-2510



Standard	IEC/EN 61921 & GB/T15576-2008
Model	New generation box type, Self healing
Power range	10kVAr
Rated voltage	250V $\pm 20\%$ (L-N)
Rated frequency	50Hz $\pm 10\%$
Rated current In	23.09A
Connection	3P+N
Reactance ratio (%)	-
Capacitance tolerance	-5% / +10%
Measurement tolerance	Voltage: $\leq \pm 0.5\%$ (0.8~1.2Un), current: $\leq \pm 0.5\%$ (0.2~1.2In) active power: $\leq \pm 2\%$, power factor: $\leq \pm 1\%$, temperature: $\pm 1^\circ\text{C}$
Communication interface	RS485
Communication protocol	Modbus protocol / DL645
Dielectric	Metallized polypropylene film with Zn/Al alloy
Impregnation	Non-PCB, biodegradable soft resin
Temperature category	- 25°C to +55°C (class D)
Max altitude	2000 m
Max relative humidity	Relative humidity $\leq 50\%$ at 40°C; $\leq 90\%$ at 20°C
Maximum permissible current	1.5 In
Maximum inrush current	200 In
Statistical life expectancy	> 130,000 Operating hours
Working mode	Continuous
Protective function	Over-voltage protection, under-voltage protection, short-circuit protection, over-current protection, over-harmonic protection, over-temperature protection, drive failure protection
Dimension WxDxH	80×395×215mm

