

Technical Datasheet

6121 CEILING LIGHT CLASSIC SERIES

The Ceiling Light Classic Series 6121 is a reliable lighting solution for balconies and bathrooms. It delivers high luminous efficacy, consistent quality, and reliable performance. Available in multiple configurations with luminous outputs from 520 lm to 2,100 lm, it features an elegant design for modern interiors.



6121 xxxY 2002

xxx = Power

Y = CCT

Input Voltage	154-250V~
Frequency	50/60Hz
Power (xxx)	006W, 010W, 017W, 020W and 024W
Correlated Color Temperature (Y = 3 or 4 or 6)	3000K (3) or 4000K (4) or 6500K (6)
Luminous Efficacy (rated) (Nom)	88lm/W
Power Factor	>0.7
Color rendering index (CRI)	>80
Luminaire light beam spread	120°
Luminous flux tolerance	+/-6%
Power consumption tolerance	+/-10%
Median useful life L70B50	25000 hours
Ambient temperature range	-20 to +40°C
Protection rating	IP44
Protection class IEC	Safety class II
Testing Authority	DEKRA

Dimensions			
Code	Power	Product Size D x H (mm)	Packing (Qty/Ctn)
6121 006Y 2002	6W	Φ225x50	12
6121 010Y 2002	10W	Φ250x50	12
6121 017Y 2002	17W	Φ320x50	18
6121 020Y 2002	20W	Φ380x50	24
6121 024Y 2002	24W	Φ380x50	24

