

# Technical Datasheet

## 6123 CEILING LIGHT SLIM SERIES

The Ceiling Light Slim Series 6123 is an ideal lighting solution for decorative spaces and bedrooms. Featuring a slim, elegant profile, it offers exceptional aesthetics, consistent quality, and reliable long-term performance. Available in multiple configurations with luminous outputs ranging from 1,500 lm to 3,600 lm, it integrates seamlessly into a wide variety of modern interior spaces.



6123 xxxY 2002  
xxx = Power  
Y = CCT

|                                                |                                     |
|------------------------------------------------|-------------------------------------|
| Input Voltage                                  | 154-250V~                           |
| Frequency                                      | 50/60Hz                             |
| Power (xxx)                                    | 015W, 018W, 022W and 036W           |
| Correlated Color Temperature (Y = 3 or 4 or 6) | 3000K (3) or 4000K (4) or 6500K (6) |
| Luminous Efficacy (rated) (Nom)                | 100lm/W                             |
| Power Factor                                   | >0.7                                |
| Color rendering index (CRI)                    | >80                                 |
| Luminaire light beam spread                    | 120°                                |
| 3-step dimming                                 | 100%, 50%, 10%                      |
| Luminous flux tolerance                        | +/-6%                               |
| Power consumption tolerance                    | +/-10%                              |
| Median useful life L70B50                      | 25000 hours                         |
| Ambient temperature range                      | -20 to +40°C                        |
| Protection rating                              | IP44                                |
| Protection class IEC                           | Safety class II                     |
| Testing Authority                              | DEKRA                               |

| Dimensions     |       |                            |                      |
|----------------|-------|----------------------------|----------------------|
| Code           | Power | Product Size<br>D x H (mm) | Packing<br>(Qty/Ctn) |
| 6123 015Y 2002 | 15W   | Φ241x23.5                  | 20                   |
| 6123 018Y 2002 | 18W   | Φ291x23.5                  | 20                   |
| 6123 022Y 2002 | 22W   | Φ421x23.5                  | 20                   |
| 6123 036Y 2002 | 36W   | Φ541x28.5                  | 10                   |

