

Technical Datasheet

6743 PREMIUM SERIES UFO LIGHT

The Premium UFO Light combines a high-quality construction with advanced thermal management, delivering superior luminous performance, enhanced durability, and exceptional lighting quality for demanding environments.



6743 xxxY 2002
xxx = Power
Y = CCT

Input Voltage	100-250V~
Frequency	50/60Hz
Power (xxx)	150W, 200W and 300W
Correlated Color Temperature (Y = 3 or 4 or 6)	3000K (3) or 4000K (4) or 6500K (6)
Luminous Efficacy (rated) (Nom)	120lm/W
Power Factor	>0.7
Color rendering index (CRI)	>80
Luminaire light beam spread	>115°
Luminous flux tolerance	+/-6%
Median useful life L70B50	50000 hours
Ambient temperature range	-20 to +40°C
Protection rating	IP65
Protection class IEC	Safety class II
Dimensions	

Code	Power	Product Size (mm)	Packing (Qty/Ctn)
6743 150Y 2002	150W	Φ385x120	4
6743 200Y 2002	200W	Φ385x120	4
6743 300Y 2002	300W	Φ385x120	4
6743 0000 2002	Aluminum Reflector for Industrial Lighting Overall dimensions of the light fixture with reflector		10

