

# Technical Datasheet

## 6917 REFLECTOR LED BULB SERIES

Featuring a directional reflector design, the Reflector LED Bulb offers focused and comfortable illumination, ideal for accent, display, and spotlight lighting applications.



6917 xxxY 2002

xxx = Power

Y = CCT

|                                                |                                     |
|------------------------------------------------|-------------------------------------|
| Input Voltage                                  | 100-250V~                           |
| Frequency                                      | 50/60Hz                             |
| Power (xxx)                                    | 020W, 030W and 040W                 |
| Correlated Color Temperature (Y = 3 or 4 or 6) | 3000K (3) or 4000K (4) or 6500K (6) |
| Luminous Efficacy (rated) (Nom)                | 90lm/W                              |
| Power Factor                                   | >0.7                                |
| Color rendering index (CRI)                    | >80                                 |
| Luminaire light beam spread                    | 115°                                |
| Luminous flux tolerance                        | +/-6%                               |
| Median useful life L70B50                      | 30000 hours                         |
| Ambient temperature range                      | -20 to +40°C                        |
| Protection rating                              | IP20                                |
| Protection class IEC                           | Safety class II                     |
| Dimensions                                     |                                     |

| Code           | Power | Base | Product Size (mm) | Packing (Qty/Ctn) |
|----------------|-------|------|-------------------|-------------------|
| 6917 020Y 2002 | 20W   | E27  | Φ130x70           | 90                |
| 6917 030Y 2002 | 30W   | E27  | Φ190x103          | 36                |
| 6917 040Y 2002 | 40W   | E27  | Φ225x130          | 10                |

