

Technical Datasheet

6918 LINEAR LED BULB SERIES

Designed to deliver efficient and uniform illumination, the Linear LED Bulb provides high brightness, energy efficiency, and long-lasting performance, making it an ideal lighting solution for narrow installation spaces.



6918 xxxY 2002

xxx = Power

Y = CCT

Input Voltage	100-250V~
Frequency	50/60Hz
Power (xxx)	004W, 007W, 009W and 012W
Correlated Color Temperature (Y = 3 or 4 or 6)	3000K (3) or 4000K (4) or 6500K (6)
Luminous Efficacy (rated) (Nom)	110lm/W
Power Factor	>0.7
Color rendering index (CRI)	>80
Luminaire light beam spread	115°
Luminous flux tolerance	+/-6%
Median useful life L70B50	30000 hours
Ambient temperature range	-20 to +40°C
Protection rating	IP20
Protection class IEC	Safety class II
Dimensions	

Code	Power	Base	Product Size (mm)	Packing (Qty/Ctn)
6918 004Y 2002	4W	E27	Φ38x111	100
6918 007Y 2002	7W	E27	Φ38x111	100
6918 009Y 2002	9W	E27	Φ45x152	100
6918 012Y 2002	12W	E27	Φ45x152	100

